

BELLOWS CAPSULE 6" LL 2-PLY



T-321 S/S MULTI-PLY

**1200° MAX EXHAUST
TEMPERATURE AT 5 PSIG***

BELLOWS I.D.	BELLOWS L/L	AXIAL COMP	LATERAL OFFSET	MP CAPSULE PART NUMBER
3.00"	6.00"	1.25"	.625"	12-3090
3.50"	6.00"	1.50"	.625"	12-3590
4.00"	6.00"	1.75"	.625"	12-4090
4.50"	6.00"	1.75"	.625"	12-4590
5.00"	6.00"	2.00"	.625"	12-5090
5.56"	6.00"	2.00"	.625"	12-5590
6.00"	6.00"	2.00"	.625"	12-6090
6.625"	6.00"	2.00"	.625"	12-6590
8.00"	6.00"	2.00"	.500"	12-8090
8.625"	6.00"	2.00"	.500"	12-8590
10.00"	6.00"	2.00"	.500"	12-10090
10.75"	6.00"	2.00"	.430"	12-10590
12.00"	6.00"	2.00"	.430"	12-12090
12.75"	6.00"	2.00"	.375"	12-12590
14.00"	6.00"	2.00"	.375"	12-14090
16.00"	6.00"	2.00"	.250"	12-16090
18.00"	6.00"	2.00"	.250"	12-18090
20.00"	6.00"	2.00"	.250"	12-20090
22.00"	6.00"	2.00"	.188"	12-22090
24.00"	6.00"	2.00"	.188"	12-24090
26.00"	6.00"	2.00"	.188"	12-26090
28.00"	6.00"	2.00"	.188"	12-28090
30.00"	6.00"	2.00"	.125"	12-30090
32.00"	6.00"	2.00"	.125"	12-32090
34.00"	6.00"	2.00"	.063"	12-34090
36.00"	6.00"	2.00"	.063"	12-36090
38.00"	6.00"	2.00"	.063"	12-38090
40.00"	6.00"	2.00"	.063"	12-40090
42.00"	6.00"	2.00"	.063"	12-42090
44.00"	6.00"	2.00"	.063"	12-44090
46.00"	6.00"	2.00"	.063"	12-46090
48.00"	6.00"	2.00"	.063"	12-48090

HASTELLOY X MULTI-PLY

**1500° MAX EXHAUST
TEMPERATURE AT 5 PSIG**

BELLOWS I.D.	BELLOWS L/L	AXIAL COMP	LATERAL OFFSET	MP CAPSULE PART NUMBER
3.00"	6.00"	1.25"	.625"	12-3000-X
3.50"	6.00"	1.25"	.625"	12-3500-X
4.00"	6.00"	1.25"	.625"	12-4000-X
4.50"	6.00"	1.75"	.625"	12-4500-X
5.00"	6.00"	2.00"	.625"	12-5000-X
5.56"	6.00"	2.00"	.625"	12-5500-X
6.00"	6.00"	2.00"	.625"	12-6000-X
6.625"	6.00"	2.00"	.625"	12-6500-X
8.00"	6.00"	2.00"	.500"	12-8000-X
8.625"	6.00"	2.00"	.500"	12-8500-X
10.00"	6.00"	2.00"	.500"	12-10000-X
10.75"	6.00"	2.00"	.430"	12-10500-X
12.00"	6.00"	2.00"	.430"	12-12000-X
12.75"	6.00"	2.00"	.375"	12-12500-X
14.00"	6.00"	2.00"	.375"	12-14000-X
16.00"	6.00"	2.00"	.250"	12-16000-X
18.00"	6.00"	2.00"	.250"	12-18000-X
20.00"	6.00"	2.00"	.250"	12-20000-X
22.00"	6.00"	2.00"	.188"	12-22000-X
24.00"	6.00"	2.00"	.188"	12-24000-X
26.00"	6.00"	2.00"	.188"	12-26000-X
28.00"	6.00"	2.00"	.188"	12-28000-X
30.00"	6.00"	2.00"	.125"	12-30000-X
32.00"	6.00"	2.00"	.125"	12-32000-X
34.00"	6.00"	2.00"	.063"	12-34000-X
36.00"	6.00"	2.00"	.063"	12-36000-X
38.00"	6.00"	2.00"	.063"	12-38000-X
40.00"	6.00"	2.00"	.063"	12-40000-X
42.00"	6.00"	2.00"	.063"	12-42000-X
44.00"	6.00"	2.00"	.063"	12-44000-X
46.00"	6.00"	2.00"	.063"	12-46000-X
48.00"	6.00"	2.00"	.063"	12-48000-X

INCONEL 625 MULTI-PLY

**1300° MAX EXHAUST
TEMPERATURE AT 5 PSIG**

BELLOWS I.D.	BELLOWS L/L	AXIAL COMP	LATERAL OFFSET	MP CAPSULE PART NUMBER
3.00"	6.00"	1.25"	.625"	12-3000-625
3.50"	6.00"	1.25"	.625"	12-3500-625
4.00"	6.00"	1.75"	.625"	12-4000-625
4.50"	6.00"	1.75"	.625"	12-4500-625
5.00"	6.00"	2.00"	.625"	12-5000-625
5.56"	6.00"	2.00"	.625"	12-5500-625
6.00"	6.00"	2.00"	.625"	12-6000-625
6.625"	6.00"	2.00"	.625"	12-6500-625
8.00"	6.00"	2.00"	.500"	12-8000-625
8.625"	6.00"	2.00"	.500"	12-8500-625
10.00"	6.00"	2.00"	.500"	12-10000-625
10.75"	6.00"	2.00"	.430"	12-10500-625
12.00"	6.00"	2.00"	.375"	12-12000-625
12.75"	6.00"	2.00"	.375"	12-12500-625
14.00"	6.00"	2.00"	.375"	12-14000-625
16.00"	6.00"	2.00"	.250"	12-16000-625
18.00"	6.00"	2.00"	.250"	12-18000-625
20.00"	6.00"	2.00"	.250"	12-20000-625
22.00"	6.00"	2.00"	.188"	12-22000-625
24.00"	6.00"	2.00"	.188"	12-24000-625
26.00"	6.00"	2.00"	.188"	12-26000-625
28.00"	6.00"	2.00"	.188"	12-28000-625
30.00"	6.00"	2.00"	.125"	12-30000-625
32.00"	6.00"	2.00"	.125"	12-32000-625
34.00"	6.00"	2.00"	.063"	12-34000-625
36.00"	6.00"	2.00"	.063"	12-36000-625
38.00"	6.00"	2.00"	.063"	12-38000-625
40.00"	6.00"	2.00"	.063"	12-40000-625
42.00"	6.00"	2.00"	.063"	12-42000-625
44.00"	6.00"	2.00"	.063"	12-44000-625
46.00"	6.00"	2.00"	.063"	12-46000-625
48.00"	6.00"	2.00"	.063"	12-48000-625

*36" T321 AND UP RATED 2 PSIG @ 1200° F OR 5 PSIG @ 1000° F

AXIAL AND LATERAL MOVEMENTS ARE NON-CONCURRENT

NOTE: TEMPERATURE RATINGS ARE FOR THE BELLOWS ELEMENT ONLY AND CONSIDERATION MUST BE GIVEN TO THE FLANGE AND FITTING MATERIALS.

