


BELLOWS CAPSULE 12" LL 2-PLY



T-321 S/S MULTI-PLY

**1200° MAX EXHAUST
TEMPERATURE AT 5 PSIG***

BELLOWS I.D.	BELLOWS L/L	AXIAL COMP	LATERAL OFFSET	MP CAPSULE PART NUMBER
4.00"	12.00"	2.00"	1.50"	12-40120
4.50"	12.00"	2.50"	1.50"	12-45120
5.00"	12.00"	3.25"	1.50"	12-50120
5.56"	12.00"	4.00"	1.50"	12-55120
6.00"	12.00"	4.50"	1.50"	12-60120
6.625"	12.00"	5.00"	1.50"	12-65120
8.00"	12.00"	5.50"	1.50"	12-80120
8.625"	12.00"	5.50"	1.50"	12-85120
10.00"	12.00"	5.50"	1.50"	12-100120
10.75"	12.00"	5.50"	1.50"	12-105120
12.00"	12.00"	5.50"	1.50"	12-120120
12.75"	12.00"	5.50"	1.50"	12-125120
14.00"	12.00"	5.50"	1.50"	12-140120
16.00"	12.00"	5.50"	1.25"	12-160120
18.00"	12.00"	5.50"	1.13"	12-180120
20.00"	12.00"	5.25"	1.00"	12-200120
22.00"	12.00"	5.25"	.875"	12-220120
24.00"	12.00"	5.25"	.750"	12-240120
26.00"	12.00"	5.25"	.750"	12-260120
28.00"	12.00"	5.25"	.750"	12-280120
30.00"	12.00"	5.25"	.625"	12-300120
32.00"	12.00"	5.25"	.625"	12-320120
34.00"	12.00"	5.25"	.500"	12-340120
36.00"	12.00"	5.25"	.500"	12-360120
38.00"	12.00"	5.25"	.500"	12-380120
40.00"	12.00"	5.25"	.500"	12-400120
42.00"	12.00"	5.25"	.500"	12-420120
44.00"	12.00"	5.25"	.500"	12-440120
46.00"	12.00"	5.25"	.375"	12-460120
48.00"	12.00"	5.25"	.375"	12-480120

HASTELLOY X MULTI-PLY

**1500° MAX EXHAUST
TEMPERATURE AT 5 PSIG**

BELLOWS I.D.	BELLOWS L/L	AXIAL COMP	LATERAL OFFSET	MP CAPSULE PART NUMBER
4.00"	12.00"	2.00"	1.75"	12-40120-X
4.50"	12.00"	2.63"	1.75"	12-45120-X
5.00"	12.00"	3.25"	1.75"	12-50120-X
5.56"	12.00"	3.75"	1.75"	12-55120-X
6.00"	12.00"	4.50"	1.75"	12-60120-X
6.625"	12.00"	4.75"	1.75"	12-65120-X
8.00"	12.00"	5.50"	1.75"	12-80120-X
8.625"	12.00"	5.50"	1.75"	12-85120-X
10.00"	12.00"	5.50"	1.75"	12-100120-X
10.75"	12.00"	5.50"	1.75"	12-105120-X
12.00"	12.00"	5.50"	1.63"	12-120120-X
12.75"	12.00"	5.50"	1.63"	12-125120-X
14.00"	12.00"	5.50"	1.50"	12-140120-X
16.00"	12.00"	5.50"	1.25"	12-160120-X
18.00"	12.00"	5.50"	1.13"	12-180120-X
20.00"	12.00"	5.25"	1.00"	12-200120-X
22.00"	12.00"	5.25"	.875"	12-220120-X
24.00"	12.00"	5.25"	.750"	12-240120-X
26.00"	12.00"	5.25"	.750"	12-260120-X
28.00"	12.00"	5.25"	.625"	12-280120-X
30.00"	12.00"	5.25"	.625"	12-300120-X
32.00"	12.00"	5.25"	.625"	12-320120-X
34.00"	12.00"	5.25"	.500"	12-340120-X
36.00"	12.00"	5.25"	.500"	12-360120-X
38.00"	12.00"	5.25"	.500"	12-380120-X
40.00"	12.00"	5.25"	.500"	12-400120-X
42.00"	12.00"	5.25"	.500"	12-420120-X
44.00"	12.00"	5.25"	.375"	12-440120-X
46.00"	12.00"	5.25"	.375"	12-460120-X
48.00"	12.00"	5.25"	.375"	12-480120-X

INCONEL 625 MULTI-PLY

**1300° MAX EXHAUST
TEMPERATURE AT 5 PSIG**

BELLOWS I.D.	BELLOWS L/L	AXIAL COMP	LATERAL OFFSET	MP CAPSULE PART NUMBER
4.00"	12.00"	2.00"	1.75"	12-40120-625
4.50"	12.00"	2.63"	1.75"	12-45120-625
5.00"	12.00"	3.25"	1.75"	12-50120-625
5.56"	12.00"	3.75"	1.75"	12-55120-625
6.00"	12.00"	4.50"	1.75"	12-60120-625
6.625"	12.00"	4.50"	1.75"	12-65120-625
8.00"	12.00"	5.50"	1.75"	12-80120-625
8.625"	12.00"	5.50"	1.75"	12-85120-625
10.00"	12.00"	5.50"	1.75"	12-100120-625
10.75"	12.00"	5.50"	1.75"	12-105120-625
12.00"	12.00"	5.50"	1.50"	12-120120-625
12.75"	12.00"	5.50"	1.50"	12-125120-625
14.00"	12.00"	5.50"	1.38"	12-140120-625
16.00"	12.00"	5.50"	1.25"	12-160120-625
18.00"	12.00"	5.50"	1.13"	12-180120-625
20.00"	12.00"	5.25"	1.00"	12-200120-625
22.00"	12.00"	5.25"	.875"	12-220120-625
24.00"	12.00"	5.25"	.750"	12-240120-625
26.00"	12.00"	5.25"	.750"	12-260120-625
28.00"	12.00"	5.25"	.625"	12-280120-625
30.00"	12.00"	5.25"	.625"	12-300120-625
32.00"	12.00"	5.25"	.625"	12-320120-625
34.00"	12.00"	5.25"	.500"	12-340120-625
36.00"	12.00"	5.25"	.500"	12-360120-625
38.00"	12.00"	5.25"	.500"	12-380120-625
40.00"	12.00"	5.25"	.500"	12-400120-625
42.00"	12.00"	5.25"	.500"	12-420120-625
44.00"	12.00"	5.25"	.375"	12-440120-625
46.00"	12.00"	5.25"	.375"	12-460120-625
48.00"	12.00"	5.25"	.375"	12-480120-625

*36" T321 AND UP RATED 2 PSIG @ 1200° F OR 5 PSIG @ 1000° F

AXIAL AND LATERAL MOVEMENTS ARE NON-CONCURRENT

NOTE: TEMPERATURE RATINGS ARE FOR THE BELLOWS ELEMENT ONLY AND CONSIDERATION MUST BE GIVEN TO THE FLANGE AND FITTING MATERIALS.

