



## ***Class 300 Steel Raised Face Slip-On Flanges***

SIZE	O.D.	I.D.	RAISED FACE DIA.	B.H.C. DIA.	B.H. DIA.	NO. B.H.	THK1	THK2	HUB DIA.	APPROX. WEIGHT
3/4"	4.63"	1.09"	1.69"	3.25"	.75"	4	.63"	.88"	1.88"	~2.4 lbs
1	4.88	1.36	2.00	3.50	.75	4	.69	1.06	2.13	3.0
1-1/4	5.25	1.70	2.50	3.88	.75	4	.75	1.06	2.50	4.5
1-1/2	6.13	1.95	2.88	4.50	.88	4	.81	1.19	2.75	6.5
2	6.50	2.44	3.62	5.00	.75	8	.88	1.31	3.31	7.0
2-1/2	7.50	2.94	4.12	5.88	.88	8	1.00	1.50	3.94	10.0
3	8.25	3.57	5.00	6.63	.88	8	1.13	1.69	4.62	13.0
4	10.00	4.57	6.19	7.88	.88	8	1.25	1.88	5.75	23.5
5	11.00	5.66	7.31	9.25	.88	8	1.38	2.00	7.00	29.0
6	12.50	6.72	8.50	10.63	.88	12	1.44	2.06	8.13	36.0
8	15.00	8.72	10.62	13.00	1.00	12	1.63	2.44	10.25	56.0
10	17.50	10.88	12.75	15.25	1.12	16	1.88	2.63	12.63	77.0
12	20.50	12.88	15.00	17.75	1.25	16	2.00	2.88	14.75	113.0
14	23.00	14.14	16.25	20.25	1.25	20	2.13	3.00	16.75	159.0
16	25.50	16.16	18.50	22.50	1.38	20	2.25	3.25	19.00	210
18	28.00	18.18	21.00	24.75	1.38	24	2.38	3.5	21.00	253
20	30.50	20.20	23.00	27.00	1.38	24	2.50	3.75	23.13	307
24	36.00	24.25	27.25	32.00	1.62	24	2.75	4.19	27.63	490